

View Online at <https://aerobasegroup.com/nsn/6625-01-049-6062>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

7.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.719 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.000 inches

**Overall Height:**

1.530 inches

**Overall Width:**

6.688 inches

**Mounting Hole Diameter:**

0.221 inches

**Scale Division Quantity:**

50 single indicator single range

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

10.0 volts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

5.750 inches

**Meter Body Width Behind Mounting Flange:**

4.834 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Red single indicator single range

**Scale Marking:**

0; 100; 200; 300; 400; 500; 600; 700; 800; 900; 1000; psi

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.222 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0