NSN 6625-01-052-3826

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-052-3826

view Online at https://aerobasegroup.com/nsn/oo25-01-052-3626
Circuit Current For Which Designed:
Dc
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches
Overall Height:
Between 1.734 inches and 1.766 inches
Overall Width:
Between 1.734 inches and 1.766 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
20 single indicator 1st range
Environmental Protection:
Cold resistant and dust resistant and fungus resistant and heat resistant and salt spray resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Lockwashers 4; nuts 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
50.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches
Movement Type:
Moving coil, permanent magnet
Background Color:

Pointer Color:

Black single indicator all ranges

White single indicator all ranges

NSN 6625-01-052-3826

Special Scale Meter - Page 2 of 2



Scale Marking:
Level db; -10; -5; 0; ber; 10 power 6; 10 power 5; 10 power 4; 10 power 3
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
4 solder lug
Special Features:
Altitude up to 50000 feet above sea level
Special Markings:
Black band from 37.7 to 50.0 ua deflection
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A310a0