NSN 6625-01-052-9484 Ammeter - Page 1 of 2



| Affilheter - Page 1 of 2 | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/6625-01-052-9484 | |
| Circuit Current For Which Designed: | |
| Ac | |
| Overall Length: | |
| 2.170 inches | |
| Mounting Hole Diameter: | |
| 0.156 inches | |
| Scale Division Quantity: | |
| 20 single indicator all ranges | |
| Overall Diameter: | |
| 3.500 inches | |
| Mounting Bolt Circle Diameter: | |
| 3.160 inches | |
| Furnished Items And Quantity: | |
| Nut 7; lockwasher 7; transducer 1 | |
| Indicator Type: | |
| Dial w/pointer | |
| Installation Design: | |
| Panel | |
| Mounting Arrangement Style: | |
| Three hole/stud bolt circle | |
| Dial Scale Marking Color: | |
| Black single indicator all ranges | |
| Accuracy In Percent: | |
| -2.0/+2.0 at full scale single indicator all ranges | |
| Meter Depth Behind Mounting Flange: | |
| 1.320 inches | |
| Meter Body Diameter Behind Mounting Flange: | |
| 2.750 inches | |
| Movement Type: | |
| Moving iron vane | |
| Background Color: | |
| White single indicator all ranges | |

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+800.0 amperes, ac single indicator 3rd range

NSN 6625-01-052-9484 Ammeter - Page 2 of 2



| Scale Selection Method: |
|---|
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |