

View Online at <https://aerobasegroup.com/nsn/6625-01-054-5717>

Circuit Current For Which Designed:

Dc

Overall Length:

1.251 inches

Overall Diameter:

1.250 inches

Furnished Items And Quantity:

O ring 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range and green single indicator single range and red single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.375 inches

Meter Body Diameter Behind Mounting Flange:

1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; .5; 1

Mounting Facility Type And Quantity:

1 threaded body and 1 threaded ring

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Markings:

Red band from 0 to .4; green band from .4 to .6; red band from .6 to 1

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0