

View Online at <https://aerobasegroup.com/nsn/6625-01-057-1816>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

3.500 inches

Overall Height:

2.560 inches

Overall Width:

3.250 inches

Mounting Hole Diameter:

0.147 inches

Scale Division Quantity:

50 single indicator single range

Distance Between Mounting Facility Centers:

1.870 inches

Barrel Width:

2.560 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.281 inches

Meter Body Width Behind Mounting Flange:

2.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket and 2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

3.840 inches

Meter Barrel Depth:

0.680 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Material:

Plastic

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0