

View Online at <https://aerobasegroup.com/nsn/6625-01-057-5324>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.820 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

32 single indicator all ranges

Overall Diameter:

3.510 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.420 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-160.0/+160.0 decibels single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Left and right at respective full scale deflections

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Round flush mtg

Supplementary Features:

Cutouts in bezel permit light on dial

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0