NSN 6625-01-062-8031

Special Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

0.515 inches

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-01-062-8031

| 1500.0 |
|---|
| Overall Length: |
| 2.720 inches |
| Overall Height: |
| 0.780 inches |
| Overall Width: |
| 2.070 inches |
| Scale Division Quantity: |
| 2 single indicator single range |
| Environmental Protection: |
| Cold resistant and dust resistant and heat resistant and humidity resistant |
| Furnished Items And Quantity: |
| Nut 4; lockwasher 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.390 inches |
| Meter Body Width Behind Mounting Flange: |
| 1.630 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Scale Marking: |
| Millirads; 0; 140; 255 |
| Mounting Facility Type And Quantity: |
| 2 bracket and 2 screw |
| Scale Graduation Type: |
| Linear single indicator single range |
| Meter Body Height Rehind Mounting Flange: |

NSN 6625-01-062-8031

Special Scale Meter - Page 2 of 2



| Features Provided: |
|---|
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug and 2 threaded stud |
| Operating Voltage Rating In Volts: |
| 12.0 dc |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, electronic systems, except specially designed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A310a0 |
| |