

View Online at https://aerobasegroup.com/nsn/6625-01-067-0783

18.750 inchesOverall Height:3.469 inchesOverall Width:16.750 inchesCurrent Type:AcFrequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:Frequency Rating:0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Positioned Decimal Point:ProvidedSolid State Feature:IncludedPing-in Units Provision:Not includedSuid State Feature:Not includedStandard Frequency Output Feature:Standard Frequency Output Feature:	
Overall Height:3.469 inchesOverall Width:16.750 inchesCurrent Type:AcFrequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMeasurement Type:FrequencyFrequency Rating:0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedPorvidedPincy In Units Provision:NicludedPincy In Units Provision:Not includedSublay Inter FrequencyProvidedRemote Control Provisions:IncludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincludedPincluded <td>Overall Length:</td>	Overall Length:
3.469 inchesOverall Width:16.750 inchesCurrent Type:AcFrequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyPrequency Rating:0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Dositioned Decimal Point:ProvidedRemote Control Provisions:IncludedPlug-in Units Provision:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	
Overall Width:16.750 inchesCurrent Type:AcFrequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequency Rating:40.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Units Indicator:IncludedDisplay Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedPlug-in Units Provision:Not includedSuld State Feature:IncludedSuld State Feature:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	-
16.750 inchesCurrent Type:AcFrequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequencyPorm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Units Indicator:IncludedDisplay Digit Quantity:8Display Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedPlug-in Units Provision:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	3.469 inches
Current Type: Ac Frequency Rating: Between 48.0 hertz and 66.0 hertz Internal Battery Accommodation: Not included Voltage Rating: 115.0 volts or 230.0 volts Output Frequency Rating: 10.0 megahertz Unpackaged Unit Weight: 25.000 pounds Mounting Method: Rack Measurement Type: Frequency Rating: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included	Overall Width:
AcFrequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMeasurement Type:Frequency Rating:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedPlug-in Units Provision:Not includedSubit State Feature:Not includedStandard Frequency Output Feature:	16.750 inches
Frequency Rating:Between 48.0 hertz and 66.0 hertzInternal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:Frequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedPlug-in Units Provision:Not includedSuld State Feature:IncludedSuld State Frequency:Not includedStandard Frequency Output Feature:	Current Type:
Between 48.0 hertz and 66.0 hertz Internal Battery Accommodation: Not included Voltage Rating: 115.0 volts or 230.0 volts Output Frequency Rating: 10.0 megahertz Unpackaged Unit Weight: 25.000 pounds Mounting Method: Rack Measurement Type: Frequency Range: 40.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Ac
Internal Battery Accommodation:Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Doitioned Decimal Point:ProvidedRemote Control Provisions:IncludedSolid State Feature:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	Frequency Rating:
Not includedVoltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Units Indicator:IncludedProvidedRemote Control Provisions:IncludedSolid State Feature:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	Between 48.0 hertz and 66.0 hertz
Voltage Rating:115.0 volts or 230.0 voltsOutput Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedSolid State Feature:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	Internal Battery Accommodation:
115.0 volts or 230.0 volts Output Frequency Rating: 10.0 megahertz Unpackaged Unit Weight: 25.000 pounds Mounting Method: Rack Measurement Type: Rrequency Frequency Frequency Range: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Display Eature: Included Plug-in Units Provision: Not included	Not included
Output Frequency Rating:10.0 megahertzUnpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Digit Quantity:1ncludedProvidedRemote Control Provisions:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	Voltage Rating:
10.0 megahertz Unpackaged Unit Weight: 25.000 pounds Mounting Method: Rack Measurement Type: Frequency Frequency Range: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included	115.0 volts or 230.0 volts
Unpackaged Unit Weight:25.000 poundsMounting Method:RackMeasurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Units Indicator:IncludedProvidedRemote Control Provisions:IncludedPlug-in Units Provision:Not includedSuld State Feature:IncludedSolid State FrequencyOut includedSuld State FrequencyStandard Frequency Output Feature:	Output Frequency Rating:
25.000 pounds Mounting Method: Rack Measurement Type: Frequency Frequency Range: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Digit Quantity: 8 Display Positioned Decimal Point: Provided Display Positioned Decimal Point: Provided Remote Control Provisions: Included Dicluded Plug-in Units Provision: Not included	10.0 megahertz
Mounting Method:RackMeasurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Units Indicator:IncludedProvidedRemote Control Provisions:IncludedPloudedPloudedNot includedSolid State Feature:Not includedStandard Frequency Output Feature:	Unpackaged Unit Weight:
Rack Measurement Type: Frequency Frequency Range: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included	25.000 pounds
Measurement Type:FrequencyFrequency Range:+0.0000001/+23.0000000 gigahertzAccuracy Rating:Porm 1 count porm time baseDisplay Type:Numeric readout tubeDisplay Digit Quantity:8Display Units Indicator:IncludedProvidedRemote Control Provisions:IncludedSolid State Feature:IncludedPlug-in Units Provision:Not includedStandard Frequency Output Feature:	Mounting Method:
Frequency Frequency Range: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Rack
Frequency Range: +0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Measurement Type:
+0.0000001/+23.0000000 gigahertz Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Frequency
Accuracy Rating: Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Frequency Range:
Porm 1 count porm time base Display Type: Numeric readout tube Display Digit Quantity: 8 Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	+0.00000001/+23.00000000 gigahertz
Display Type:Numeric readout tubeDisplay Digit Quantity:8Display Units Indicator:IncludedDisplay Positioned Decimal Point:ProvidedRemote Control Provisions:IncludedSolid State Feature:IncludedProvidedSolid State Feature:IncludedSolid State Feature:Not includedStandard Frequency Output Feature:	Accuracy Rating:
Numeric readout tube Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Porm 1 count porm time base
Display Digit Quantity: 8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Display Type:
8 Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Numeric readout tube
Display Units Indicator: Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Display Digit Quantity:
Included Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	8
Display Positioned Decimal Point: Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Display Units Indicator:
Provided Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Included
Remote Control Provisions: Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Display Positioned Decimal Point:
Included Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Provided
Solid State Feature: Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Remote Control Provisions:
Included Plug-in Units Provision: Not included Standard Frequency Output Feature:	Included
Plug-in Units Provision: Not included Standard Frequency Output Feature:	Solid State Feature:
Not included Standard Frequency Output Feature:	Included
Standard Frequency Output Feature:	Plug-in Units Provision:
	Not included
	Standard Frequency Output Feature:
Included	Included



Output Frequency Waveform:

Square wave

Frequency Output Amplitude:

2.4 volts peak to peak

Special Features:

Hi-stability time base, rear panelconnectors; rack flange kit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T297-a