

View Online at <https://aerobasegroup.com/nsn/6625-01-067-1129>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Overall Height:

0.730 inches

Overall Width:

2.310 inches

Mounting Hole Diameter:

0.136 inches

Distance Between Mounting Facility Centers:

2.000 inches

Barrel Width:

0.935 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.450 inches

Meter Body Width Behind Mounting Flange:

2.250 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

Snr; -infinity; -10; -5; 0; +5; +10; +15; +20; +infinity

Mounting Facility Type And Quantity:

1 flange and 2 screw and 2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Meter Body Height Behind Mounting Flange:

1.120 inches

Meter Barrel Depth:

0.935 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Screws work as clamp to press panel to flange

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Supplementary Features:

Horizontal mount

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0