

View Online at <https://aerobasegroup.com/nsn/6625-01-067-7306>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1100.0

Overall Length:

3.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.270 inches

Overall Width:

3.130 inches

Scale Division Quantity:

50 single indicator 1st range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Term. Hdw 2; mtg hdw 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+90.000/+150.000 hertz

Sensitivity Rating:

25.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.010 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Ddm; -.020; -.015; -.010; -.005; 0; .005; .010; .015; .020; pct mod; 0; 10; 20; 30; 40; 50

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Mounting Stud Diameter:

0.112 inches

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Self contained

Special Markings:

90 hz; 150 hz

Material:

Plastic or steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint lusterless

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0