

View Online at <https://aerobasegroup.com/nsn/6625-01-069-1257>

Inclosure Material:

Aluminum

Overall Length:

21.440 inches

Overall Height:

14.060 inches

Overall Width:

20.810 inches

Vibration Resistance Range In Hertz:

Not rated

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

Not rated

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

Sg-1158/u-80058

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Portable

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

1.1 kilohertz operating channel err-100

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

10.000 volts interstage preset

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Pulse Peak Amplitude Per Channel:

Not rated

Signal Data Type Per Channel:

Operating channel radio frequency

Maximum Continuous Operating Time In Hours:

Not rated

Operating Ac Frequency In Hertz:

50.0 single voltage

External Ac Operating Voltage In Volts:

115.0 single voltage

Phase:

Single

Functional Classification:

Bb-2.1

Functional Description:

Used to simulate serial data characteristics required for use in maintaining an/usm-448, an/usm-442, mx-9942/u, mx-9941/u, mx-9940/u, mx-9938/u, an/usm-446 and an/arm-183

Entry Date:

80-10-01

Reference Data And Literature:

To 33a1-8-852-1

Type/model Designation:

Sg-1158u

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200