

View Online at <https://aerobasegroup.com/nsn/6625-01-070-4055>

Circuit Current For Which Designed:

Dc

Overall Length:

2.650 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

40 single indicator all ranges

Overall Diameter:

2.695 inches

Environmental Protection:

Cold resistant and heat resistant and watertight

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 volts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+50.0 volts single indicator 1st range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Conforms to mil-m-10304, type mr26w---dcvvr

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0