NSN 6625-01-070-7499

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-070-7499

Circuit Current For Which Designed:

Dc

Overall Length:

1.960 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches

Overall Height:

2.250 inches

Overall Width:

3.000 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.437 inches

Environmental Protection:

Dust resistant and humidity resistant

Furnished Items And Quantity:

Nut 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.907 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-01-070-7499

Ammeter - Page 2 of 2



Power Source: External Mounting Facility Type And Quantity: 4 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+20.0 amperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches **Features Provided:** Knife edge pointer and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Markings:** Sign on rear of case Material: Plastic acrylic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint **Style Designator:** Rectangular flush mtg **Supplementary Features:** Clear plastic snap-off bezel **Fsc Application Data:** Test set, electronic equipment Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A310a0