## NSN 6625-01-071-5314

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-071-5314

View Online at https://aerobasegroup.com/nsn/6625-01-0/1-5314
Circuit Current For Which Designed:
Ac and dc
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.306 inches and 1.318 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.306 inches and 1.318 inches
Overall Height:
1.810 inches
Overall Width:
1.810 inches
Mounting Hole Diameter:
Between 0.122 inches and 0.130 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 4; lockwasher 4; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches
Movement Type:

**Background Color:** 

White single indicator single range

Moving coil, permanent magnet

Pointer Color:

Black single indicator all ranges

## NSN 6625-01-071-5314

Voltmeter - Page 2 of 2



Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
+0.0/+30.0 volts, dc single indicator 2nd range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Phosphorescent green indicator needle; ruggedized
Special Markings:
Phosphorescent green from 12 to 15 volts dc
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0