

View Online at <https://aerobasegroup.com/nsn/6625-01-073-3011>

Circuit Current For Which Designed:

Ac

Overall Length:

2.556 inches

Overall Height:

3.615 inches

Overall Width:

4.303 inches

Mounting Hole Diameter:

0.125 inches

Environmental Protection:

Dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

3.500 inches

Furnished Items And Quantity:

Nut 2; lockwasher 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

5.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.162 inches

Meter Body Diameter Behind Mounting Flange:

3.383 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+5.0 amperes, ac single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Mirror scale and rectifier circuit and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0