NSN 6625-01-073-3011

Ammeter - Page 1 of 2

2 screw and 2 unthreaded hole

Ac

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-073-3011

Overall Length:
2.556 inches
Overall Height:
3.615 inches
Overall Width:
4.303 inches
Mounting Hole Diameter:
0.125 inches
Environmental Protection:
Dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
3.500 inches
Furnished Items And Quantity:
Nut 2; lockwasher 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Two hole/stud
Sensitivity Rating:
5.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.162 inches
Meter Body Diameter Behind Mounting Flange:
3.383 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:

NSN 6625-01-073-3011

Ammeter - Page 2 of 2



Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
+0.0/+5.0 amperes, ac single indicator 1st range
Scale Selection Method:
Terminal
Features Provided:
Mirror scale and rectifier circuit and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A310a0