

View Online at <https://aerobasegroup.com/nsn/6625-01-074-2423>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.670 inches

Overall Height:

0.500 inches

Overall Width:

1.810 inches

Scale Division Quantity:

40 single indicator 2nd range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.140 inches

Meter Body Width Behind Mounting Flange:

1.690 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Scale Marking:

Top scale: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10; bot scale: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10

Mounting Facility Type And Quantity:

2 bracket and 2 screw

Scale Graduation Type:

Nonlinear single indicator 1st range

Meter Body Height Behind Mounting Flange:

0.500 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0