NSN 6625-01-077-9657

Ammeter - Page 1 of 2

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-077-9657

Overall Length:
2.175 inches
Scale Division Quantity:
25 single indicator single range
Overall Diameter:
2.192 inches
Furnished Items And Quantity:
Nut 8; washer 6
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.182 inches
Meter Body Diameter Behind Mounting Flange:
2.079 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
1 clamp and 4 screw
1 clamp and 4 screw
1 clamp and 4 screw Scale Graduation Type:
1 clamp and 4 screw Scale Graduation Type: Linear single indicator single range
1 clamp and 4 screw Scale Graduation Type: Linear single indicator single range Measurement Range:
1 clamp and 4 screw Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+50.0 amperes single indicator single range
1 clamp and 4 screw Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+50.0 amperes single indicator single range Features Provided:
1 clamp and 4 screw Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+50.0 amperes single indicator single range Features Provided: Zero adjuster
1 clamp and 4 screw Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+50.0 amperes single indicator single range Features Provided: Zero adjuster Movement Suspension Method:

NSN 6625-01-077-9657

Ammeter - Page 2 of 2



Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A310a0