## NSN 6625-01-079-0529

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-079-0529

| Circuit Current For Which Designed:                                       |
|---|
| Dc  |
| Overall Length:   |
| 2.400 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.240 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.240 inches  |
| Overall Height:   |
| 3.250 inches  |
| Overall Width:  |
| 3.250 inches  |
| Mounting Stud Length:   |
| 0.540 inches  |
| Installation Design:  |
| Panel   |
| Mounting Arrangement Style:   |
| Four hole/stud rectangular/square   |
| Dial Scale Marking Color:   |
| Black single indicator single range                                       |
| Accuracy In Percent:  |
| -2.0/+2.0 at full scale single indicator all ranges                       |
| Meter Depth Behind Mounting Flange:                                       |
| 1.080 inches  |
| Meter Body Diameter Behind Mounting Flange:                               |
| 2.730 inches  |
| Movement Type:  |
| Moving coil, permanent magnet   |
| Background Color:   |
| White single indicator single range                                       |
| Mounting Facility Type And Quantity:                                      |
| 4 threaded stud   |
| Measurement Range:  |
| +0.0/+50.0 millivolts, dc single indicator single range                   |
| Mounting Stud Diameter:   |
| 0.112 inches  |
| Features Provided:  |
| Zero adjuster   |
| Movement Suspension Method:   |
| lowed pivet have  |

2 threaded stud

**Circuit Attachment Method And Quantity:** 

## NSN 6625-01-079-0529

Voltmeter - Page 2 of 2



| М |  |  |  |
|---|--|--|--|

Plastic

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0