

View Online at <https://aerobasegroup.com/nsn/6625-01-080-1979>

Circuit Current For Which Designed:

Dc

Overall Length:

1.882 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.318 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

1.759 inches

Overall Width:

2.243 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.498 inches

Environmental Protection:

Cold resistant and dust resistant and fungus resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Shunt wire 1; nut 6; lockwasher 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

5.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.303 inches

Meter Body Diameter Behind Mounting Flange:

1.481 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+100.0 microamperes, dc single indicator single range

Mounting Stud Diameter:

0.102 inches

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0