

View Online at <https://aerobasegroup.com/nsn/6625-01-080-3445>

Circuit Current For Which Designed:

Ac or dc

Overall Depth:

9.000 inches

Overall Height:

2.700 inches

Overall Width:

8.400 inches

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Furnished Items And Quantity:

Power line; test lead 2

Indicator Type:

Digital display

Installation Design:

Bench

Background Color:

Red single indicator all ranges

Power Source:

External or internal

Display Type:

Light emitting diode

Display Digit Quantity:

3-1/2

Measurement Range:

+0.0/+10.0 amperes, ac single indicator 1st range+0.0/+10.0 amperes, dc single indicator 2nd range+0.0/+20.0 megohms single indicator 3rd range-60.0/+600.0 volts, ac single indicator 4th range-1000.0/+1000.0 volts, dc single indicator 5th range

Scale Selection Method:

Switch

Features Provided:

Electrical overload protection and internal battery accommodation and portable

Accuracy Rating:

Porm 1.5 pct of reading plus 2 digits single indicator 1st rangeform 0.5 pct of reading plus 1 digit single indicator 2nd rangeform 0.5 pct of reading plus 1 digit single indicator 3rd rangeform 0.5 pct of reading plus 2 digits single indicator 4th rangeform 0.1 pct of reading plus 1 digit single indicator 5th range

Display Color:

Red single indicator all ranges

Circuit Attachment Method And Quantity:

4 banana jack and 1 pin jack

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Portable w/tilt view handle

Fsc Application Data:

Elec. elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0