NSN 6625-01-081-5701

+0.0/+5.0 amperes, ac single indicator single range

Power Factor Meter - Page 1 of 2

Circuit Current For Which Designed:

Ac

Overall Length: 7.020 inches

3.375 inches

3.375 inches



View Online at https://aerobasegroup.com/nsn/6625-01-081-5701

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

| Overall Height: |
|---|
| 4.310 inches |
| Overall Width: |
| 4.310 inches |
| Mounting Hole Diameter: |
| 0.250 inches |
| Scale Division Quantity: |
| 6 single indicator single range |
| Frequency Rating: |
| Between 50.0 hertz and 60.0 hertz |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 5.0 amperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0/+1.0 at full scale single indicator single range |
| Movement Type: |
| Electrostatic |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |

NSN 6625-01-081-5701

Power Factor Meter - Page 2 of 2

A310a0



| Accuracy Rating: |
|--|
| Porn 1 pct reading full scale single indicator single range |
| Display Color: |
| White single indicator single range or black single indicator single range |
| Circuit Attachment Method And Quantity: |
| 4 wire lead |
| Operating Voltage Rating In Volts: |
| 120.0 ac |
| Phase: |
| Three |
| Special Features: |
| USEO-NG-ENE-RATO |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular surface mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |