

View Online at <https://aerobasegroup.com/nsn/6625-01-085-2100>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

11.000 inches

**Overall Height:**

5.200 inches

**Overall Width:**

8.400 inches

**Frequency Rating:**

Between 48.0 hertz and 66.0 hertz and 360.0 hertz and 440.0 hertz

**Furnished Items And Quantity:**

Hp pn 00730a 5 ft. Cable for power sensor; 7.5 ft. Cable, main plugs

**Indicator Type:**

Digital display

**Installation Design:**

Cabinet

**Frequency Response Range:**

+100.000 to 50000000.000 kilohertz

**Power Source:**

External

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

4

**Measurement Range:**

-70.0 to 44.0 decibels above or below one milliwatt single indicator single range

**Scale Selection Method:**

Switch

**Features Provided:**

Zero adjuster

**Accuracy Rating:**

Porm 5.0 pct single indicator single range

**Operating Voltage Rating In Volts:**

100.0 ac and 120.0 ac and 220.0 ac and 240.0 ac

**Phase:**

Single

**Special Features:**

Opt 022 is digital input/output, fully compatible w/hp-ib; opt 004 is delete power sensor cable

**Style Designator:**

D1 rectangular or square

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0