

| NSN 6625-01-085-4684 Ammeter - Page 1 of 2 | AeroBase Group |
|---|-------------------|
| View Online at https://aerobasegroup.com/nsn/6625-01-085-4684 | |
| Circuit Current For Which Designed: | |
| Ac | |
| Overall Length: | |
| 2.524 inches | |
| Scale Division Quantity: | |
| 4 single indicator single range | |
| Overall Diameter: | |
| 2.063 inches | |
| Furnished Items And Quantity: | |

Nut 3; washer 3; insul 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.995 inches

Meter Body Diameter Behind Mounting Flange:

2.076 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-60.0/+60.0 amperes single indicator single range

Features Provided:

Self-illumination facility and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 threaded stud

NSN 6625-01-085-4684

Ammeter - Page 2 of 2



| Material: |
|-------------------------------------|
| Copper alloy |
| Nuclear Hardness Critical Feature |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Supplementary Features: |
| 2 of ckt atch studs part of mtg hdw |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A310a0