

View Online at <https://aerobasegroup.com/nsn/6625-01-088-5606>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.000 inches

Scale Division Quantity:

50 single indicator all ranges

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

150.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+50.0 volts, dc single indicator 1st range

Features Provided:

Magnetic shield

Criticality Code Justification:

Feat

Movement Suspension Method:

Metal pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Critical application

Special Markings:

Sealed-do not open

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Ruggedized

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0