NSN 6625-01-089-2957

Multimeter - Page 1 of 2

Dc

Overall Length: 2.100 inches

Mounting Hole Diameter:

Linear single indicator all ranges

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-089-2957

| 0.125 inches |
|---|
| Scale Division Quantity: |
| 20 single indicator 1st range |
| Overall Diameter: |
| 2.695 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Mounting Bolt Circle Diameter: |
| 2.560 inches |
| Furnished Items And Quantity: |
| Mtg hdw 3 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.660 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.210 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 screw and 3 unthreaded hole |
| Scale Graduation Type: |

NSN 6625-01-089-2957

Multimeter - Page 2 of 2



| Measurement Range: |
|--|
| +0.0/+2.0 kiloamperes, dc single indicator 1st range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |
| Special Features: |
| Ruggedized |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Paint |
| Special Test Features: |
| Meets mil-m-10304 requirements |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |