NSN 6625-01-093-6750

Special Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

Black single indicator all ranges

Ac



View Online at https://aerobasegroup.com/nsn/6625-01-093-6750

| Overall Length: |
|---|
| 2.200 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.880 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.880 inches |
| Overall Height: |
| 2.270 inches |
| Overall Width: |
| 2.990 inches |
| Scale Division Quantity: |
| 50 single indicator all ranges |
| Mounting Stud Length: |
| 0.500 inches |
| Environmental Protection: |
| Cold resistant and heat resistant and shock resistant and vibration resistant |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Frequency Response Range: |
| +90.000/+150.000 hertz |
| Sensitivity Rating: |
| 50.0 microamperes |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -1.0/+1.0 at 1/2 scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.300 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.140 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |

NSN 6625-01-093-6750

Special Scale Meter - Page 2 of 2



| Scale Marking: |
|--|
| $ Ddm; upper \ range: \25; \2; \15; \1; \05; \ 0; \ .05; \ .1; \ .15; \ .2; \ .25; \ lower \ range: \5; \4; \3; \2; \1; \ 0; \ 1; \ 2; \ 3; \ 4; \ 5; \2; \ -$ |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Mounting Stud Diameter: |
| 0.112 inches |
| Features Provided: |
| Mirror scale and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| 700 ohms resistance |
| Special Markings: |
| 155 and .155 w/line to scale; 90 hz left end; 150 hz right end |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Special Test Features: |
| Meets mil-t-21200, mil-t-945 and usa standard c-39.1 environmental requirements |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |