NSN 6625-01-095-9180

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-095-9180

| Circuit Current For Which Designed: |
|---|
| Dc |
| Overall Length: |
| 10.125 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.376 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.376 inches |
| Overall Height: |
| 8.750 inches |
| Overall Width: |
| 8.750 inches |
| Scale Division Quantity: |
| 40 single indicator single range |
| Mounting Stud Length: |
| 0.625 inches |
| Furnished Items And Quantity: |
| Lock washers 4; hex nuts 4 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.5/+1.5 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 9.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.980 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |

4 threaded stud

Mounting Facility Type And Quantity:

External

NSN 6625-01-095-9180

Ammeter - Page 2 of 2



| Scale Graduation Type: |
|--|
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+20.0 milliamperes, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.250 inches |
| Scale Selection Method: |
| Terminal |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Test Data Document: |
| 81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-m-16034/18 government specification |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Departure From Cited Document: |
| As modified by the measurement range per indicator |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |
| |