

View Online at <https://aerobasegroup.com/nsn/6625-01-097-1492>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

1.355 inches

Overall Height:

1.640 inches

Overall Width:

1.980 inches

Mounting Hole Diameter:

0.138 inches

Distance Between Mounting Facility Centers:

1.250 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.820 inches

Meter Body Diameter Behind Mounting Flange:

1.360 inches

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+15.0/+35.0 decibels above or below one milliwatt single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Markings:

Man set at 40; sig str; 0 dbm equals 1 mw

Material:

Plastic acrylic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets requirements of ansi c39.1

Style Designator:

Fan shape flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0