

View Online at <https://aerobasegroup.com/nsn/6625-01-097-9200>

Overall Length:

19.700 inches

Overall Height:

6.900 inches

Overall Width:

12.900 inches

Ac Voltage Rating:

Between 90.0 volts and 250.0 volts

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Frequency Range Rating:

+0.001/+1800.000 megahertz

End Application:

Electronic test equipment

Furnished Items And Quantity:

115 volt power cord, 6 ft n to n connectors 50 ohm coaxial cable, 18 in. Bnc to bnc connectors 50 ohm coaxial cable, n male to bnc female adapter, cord clamp, two 4 amp fast blow fuse, 2 amp fast blow fuse, crt visor, crt mesh filter, blue crt light filter, amber crt light filter, gray crt light filter; includes digital storage

Unit Type:

Standard

Frequency Calibration Accuracy Range In Percent:

-0.2/+0.2

Mounting Method:

Bench

Plug-in Unit Quantity:

2

Phase:

Single

Special Features:

Opt tr-503 is tek tracking generator; crt readout displays reference level, frequency, freq span/div, vertical display, rf attenuation. Resolution bandwidth; operating temp: m15 degrees c/p55 degrees c; non-operating temp: m62 degrees c/p75 degrees c; humidity: operating 95 pct; rain resistance: drip proof at 16 liters/hour/sq ft; operating altitude: 15,000 ft; vibration: 15 hz-55 hz at 0.025 in. Excursion; shock: 30 g of half sine 11 ms duration; drop: 12 in.

Reference Data And Literature:

Tek 84 data catalg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A532p0