## NSN 6625-01-099-3794

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-099-3794

Circuit Current For Which Decimod
Circuit Current For Which Designed:
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
10 single indicator single range
Environmental Protection:
Vibration proof
Furnished Items And Quantity:
Gasket 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
220.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches
Movement Type:

Moving coil, permanent magnet

## NSN 6625-01-099-3794

Ammeter - Page 2 of 2



**Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 unthreaded hole Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+100.0 microamps single indicator single range **Scale Selection Method:** Terminal **Features Provided:** Zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder lug **Special Features:** Ruggedized **Nuclear Hardness Critical Feature:** Nonhardened **Special Test Features:** Conforms to mil-m-10304 Style Designator: Rectangular flush mtg **Supplementary Features:** Moisture resistant **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A310a0