NSN 6625-01-099-3794

Ammeter - Page 1 of 2

Moving coil, permanent magnet



View Online at https://aerobasegroup.com/nsn/6625-01-099-3794

are to a section of the section of
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
10 single indicator single range
Environmental Protection:
Vibration proof
Furnished Items And Quantity:
Gasket 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
220.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches
Movement Type:

NSN 6625-01-099-3794

Ammeter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+100.0 microamps single indicator single range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Ruggedized Nuclear Hardness Critical Feature:
Nuclear Hardness Critical Feature:
Nuclear Hardness Critical Feature: Nonhardened
Nuclear Hardness Critical Feature: Nonhardened Special Test Features:
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator:
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features:
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data:
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data: Test set, elect. Equip.
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data: Test set, elect. Equip. Shelf Life:
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure:
Nuclear Hardness Critical Feature: Nonhardened Special Test Features: Conforms to mil-m-10304 Style Designator: Rectangular flush mtg Supplementary Features: Moisture resistant Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization: