

View Online at <https://aerobasegroup.com/nsn/6625-01-100-4355>

Circuit Current For Which Designed:

Dc

Overall Length:

2.945 inches

Overall Height:

0.910 inches

Overall Width:

2.145 inches

Mounting Stud Length:

0.500 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration proof

Distance Between Mounting Facility Centers:

1.907 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1225.0 ohms per volt

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.993 inches

Meter Body Width Behind Mounting Flange:

1.710 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Yellow single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+200.0 microamperes, dc single indicator single range

Mounting Stud Diameter:

0.120 inches

Meter Body Height Behind Mounting Flange:

0.610 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 turret

Special Features:

Edgewise mounting

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel lusterless

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0