

View Online at <https://aerobasegroup.com/nsn/6625-01-100-4355>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.945 inches

**Overall Height:**

0.910 inches

**Overall Width:**

2.145 inches

**Mounting Stud Length:**

0.500 inches

**Environmental Protection:**

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration proof

**Distance Between Mounting Facility Centers:**

1.907 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

1225.0 ohms per volt

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.993 inches

**Meter Body Width Behind Mounting Flange:**

1.710 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

Yellow single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+200.0 microamperes, dc single indicator single range

**Mounting Stud Diameter:**

0.120 inches

**Meter Body Height Behind Mounting Flange:**

0.610 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 turret

**Special Features:**

Edgewise mounting

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0