NSN 6625-01-100-6027

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-100-6027

Circuit Current For Which Designed:
Dc
Overall Length:
7.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.050 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
1.540 inches
Overall Width:
6.720 inches
Scale Division Quantity:
48 single indicator single range
Mounting Stud Length:
1.270 inches
Environmental Protection:
Dripproof and humidity resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Mtg hdw 4; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
White single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.840 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator single range
Pointer Color:

White single indicator single range

NSN 6625-01-100-6027

Special Scale Meter - Page 2 of 2



Scale Marking:
Knots; astern; m 18; m 15; m 10; m 5; 0; 5; 10; 15; 20; 25; 30 $$
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Mounting Stud Diameter:
0.190 inches
Meter Body Height Behind Mounting Flange:
1.225 inches
Features Provided:
Self-illumination facility and zero adjuster
Criticality Code Justification:
Feat
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Operating Voltage Rating In Volts:
28.0 dc
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Special Test Features:
Conforms to mil-m-24359
Style Designator:
Rectangular flush mtg
Supplementary Features:
Mounted 15 degrees from horizontal
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A310a0