NSN 6625-01-100-9872

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-100-9872

New Online at https://aeiobasegroup.com/nsi//do25-01-100-9672
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
7.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.050 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
1.540 inches
Overall Width:
6.720 inches
Scale Division Quantity:
50 single indicator single range
Mounting Stud Length:
1.270 inches
Environmental Protection:
Dripproof and humidity resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Mtg hdw 4; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
5.840 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:

Moving coil, permanent magnet

NSN 6625-01-100-9872

Special Scale Meter - Page 2 of 2



Background Color: White single indicator single range **Pointer Color:** Red single indicator single range Scale Marking: Psig; 0; 5; 10; 15; 20; 25; 30; 35; 40; 45; 50 **Mounting Facility Type And Quantity:** 4 threaded stud Scale Graduation Type: Linear single indicator single range **Mounting Stud Diameter:** 0.190 inches Meter Body Height Behind Mounting Flange: 1.225 inches **Features Provided:** Magnetic shield and zero adjuster **Criticality Code Justification:** Astw **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened **Special Test Features:** Conforms to mil-m-24359 Style Designator: Rectangular flush mtg **Supplementary Features:** Vertical mount **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A310a0