

View Online at <https://aerobasegroup.com/nsn/6625-01-101-1820>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

10.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

4.500 inches

Overall Width:

4.500 inches

Mounting Hole Diameter:

0.250 inches

Mounting Stud Length:

0.625 inches

Furnished Items And Quantity:

Nuts 8

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

9.000 inches

Meter Body Diameter Behind Mounting Flange:

4.000 inches

Movement Type:

Moving coil, permanent magnet and moving iron vane and moving magnet

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

1 flange and 4 threaded stud

Measurement Range:

+0.0/+300.0 amperes, ac single indicator single range

Features Provided:

Electrical overload protection and magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Style Designator:

Rectangular flush mtg

Test Data Document:

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0