NSN 6625-01-102-4196

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-102-4196

Circuit Current For Which Designed: Dc Overall Length: 3.270 inches Overall Height: 0.780 inches Overall Width: 2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range: -1.999/+1.999 volts single indicator single range
Overall Length: 3.270 inches Overall Height: 0.780 inches Overall Width: 2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
3.270 inches Overall Height: 0.780 inches Overall Width: 2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Overall Height: 0.780 inches Overall Width: 2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
O.780 inches Overall Width: 2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Overall Width: 2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
2.410 inches Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Environmental Protection: Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Shock resistant and vibration resistant Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Indicator Type: Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Dial w/pointer Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Installation Design: Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Panel Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Meter Body Width Behind Mounting Flange: 2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
2.250 inches Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Power Source: External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
External Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Mounting Facility Type And Quantity: 4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
4 clamp Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
Display Digit Quantity: 3-1/2 Measurement Range:
3-1/2 Measurement Range:
Measurement Range:
_
-1.999/+1.999 volts single indicator single range
Meter Body Height Behind Mounting Flange:
0.610 inches
Accuracy Rating:
Porm 0.1 pct of reading porm 0.05 pct full scale single indicator single range
Circuit Attachment Method And Quantity:
1 printed circuit
Special Features:
Ruggedized
Material:
Plastic and steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.

NSN 6625-01-102-4196

Voltmeter - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0