

View Online at <https://aerobasegroup.com/nsn/6625-01-102-5016>

Circuit Current For Which Designed:

Ac

Overall Length:

4.156 inches

Overall Height:

4.312 inches

Overall Width:

4.312 inches

Frequency Rating:

60.0 hertz

Environmental Protection:

Shock resistant and vibration resistant

End Application:

Ships service generator switchboard onboard 140 ft wtgb class coast guard vessels

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Frequency Response Range:

+40.000/+70.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.781 inches

Meter Body Diameter Behind Mounting Flange:

3.968 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+400.0 volts single indicator single range

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 threaded stud

Operating Voltage Rating In Volts:

400.0 ac

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies with ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0