NSN 6625-01-106-1295

Ammeter - Page 1 of 1

A310a0



View Online at https://aerobasegroup.com/nsn/6625-01-106-1295

Circuit Current For Which Designed:
Dc
Overall Length:
3.260 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.474 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.474 inches
Overall Width:
3.260 inches
Mounting Hole Diameter:
0.170 inches
Scale Division Quantity:
1 single indicator single range
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
0.690 inches
Meter Body Diameter Behind Mounting Flange:
3.000 inches
3.000 inches Background Color:
Background Color:
Black single indicator single range
Background Color: Black single indicator single range Mounting Facility Type And Quantity:
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range:
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity:
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud Style Designator:
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Rectangular flush mtg
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Rectangular flush mtg Shelf Life:
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Rectangular flush mtg Shelf Life: N/a
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Rectangular flush mtg Shelf Life: N/a
Background Color: Black single indicator single range Mounting Facility Type And Quantity: 4 unthreaded hole Measurement Range: +0.0/+5.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Rectangular flush mtg Shelf Life: N/a Unit Of Measure: