

View Online at <https://aerobasegroup.com/nsn/6625-01-106-2636>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

3.500 inches

Overall Height:

0.770 inches

Overall Width:

2.578 inches

Furnished Items And Quantity:

Nut 2; lockwasher 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.625 inches

Meter Body Width Behind Mounting Flange:

2.578 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

L; 90; 60; 55; 50; 45; 40; 35; 30; 25; 20; 15; 10; 5; 0; 5; 10; 15; 20; 25; 30; 35; 40; 45; 50; 55; 60; 90; r

Mounting Facility Type And Quantity:

1 bracket

Scale Graduation Type:

Nonlinear single indicator single range

Meter Body Height Behind Mounting Flange:

0.770 inches

Features Provided:

Magnetic shield and self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Meter reads zero to ninety degrees left and zero to ninety degrees right

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0