

View Online at <https://aerobasegroup.com/nsn/6625-01-106-7188>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

25 single indicator single range

Overall Diameter:

3.510 inches

Environmental Protection:

Heat resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hardware included

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+360.000/+440.000 hertz

Sensitivity Rating:

100.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; 25; 50; 75; 100; 125; percent rated amp

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A310a0