NSN 6625-01-107-1062

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-107-1062

Circuit Current For Which Designed:

Ac

Overall Length:

5.710 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.360 inches and 3.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.360 inches and 3.390 inches

Overall Height:

4.330 inches

Overall Width:

4.330 inches

Mounting Hole Diameter:

0.313 inches

Scale Division Quantity:

60 single indicator single range

Frequency Rating:

60.0 hertz

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+40.000/+70.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.790 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

NSN 6625-01-107-1062

Ammeter - Page 2 of 2

Black single indicator single range

Mounting Facility Type And Quantity:

Pointer Color:

Power Source:

4 unthreaded hole

Scale Graduation Type:

Measurement Range:

External



Features Provided: Magnetic shield and zero adjuster

+0.0/+1200.0 amperes, ac single indicator single range

Movement Suspension Method:

Linear single indicator single range

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel lusterless

Special Test Features:

Complies with specification ansi c-39.1

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A310a0