

View Online at <https://aerobasegroup.com/nsn/6625-01-108-4969>

Circuit Current For Which Designed:

Dc

Overall Length:

2.219 inches

Mounting Stud Length:

0.910 inches

Overall Diameter:

2.300 inches

Environmental Protection:

Cold resistant and dustproof and heat resistant

Distance Between Mounting Facility Centers:

1.500 inches

Furnished Items And Quantity:

Mtg hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

16.0 volts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.429 inches

Meter Body Diameter Behind Mounting Flange:

2.065 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket and 2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+10.0/+16.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.164 inches

Scale Selection Method:

Terminal

Features Provided:

Jaw insulation and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

12.0 dc

Special Features:

Mounted at 45 degrees tilt from vertical

Special Markings:

Battery; image of battery

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Supplementary Features:

Suitable for heavy duty off highway applications

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0