

View Online at <https://aerobasegroup.com/nsn/6625-01-108-6560>

Circuit Current For Which Designed:

Dc

Overall Length:

1.875 inches

Overall Height:

2.688 inches

Overall Width:

3.938 inches

Mounting Stud Length:

0.625 inches

Distance Between Mounting Facility Centers:

2.938 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

2.125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+25.0 amperes, rf single indicator 1st range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Metal pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

115.0 ac

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0