

View Online at <https://aerobasegroup.com/nsn/6625-01-110-9909>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

500.0

**Overall Length:**

3.300 inches

**Overall Height:**

1.520 inches

**Overall Width:**

2.910 inches

**Environmental Protection:**

Corrosion resistant and shock resistant and vibration resistant

**End Application:**

1290-01-306-7363 panel, control, electronic

**Furnished Items And Quantity:**

Screw 4; nut 2; washer 8

**Indicator Type:**

Digital display

**Installation Design:**

Panel

**Sensitivity Rating:**

4.0 megohm per volt

**Meter Depth Behind Mounting Flange:**

2.710 inches

**Meter Body Width Behind Mounting Flange:**

2.760 inches

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 bracket and 2 screw

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

4-1/2

**Measurement Range:**

-199.99/+199.99 millivolts single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.230 inches

**Features Provided:**

Zero adjuster

**Accuracy Rating:**

Porm 0.05 pct of reading porm 0.01 pct full scale single indicator single range

**Display Color:**

Red single indicator single range

**Circuit Attachment Method And Quantity:**

1 printed circuit

**Operating Voltage Rating In Volts:**

Between 4.8 dc and 6.0 dc

**Special Features:**

Ruggedized

**Special Markings:**

Pins on connector are indeseed by row: a, 1 through 15; b, 1 through 15

**Material:**

Plastic and steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Electrical, electronic properities measuring and test instuments

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0