

View Online at <https://aerobasegroup.com/nsn/6625-01-111-4295>

Circuit Current For Which Designed:

Ac

Overall Length:

2.850 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

75 single indicator single range

Overall Diameter:

3.510 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 7; washer 7

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+150.0 amperes, ac single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304b

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0