

View Online at <https://aerobasegroup.com/nsn/6625-01-111-4401>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 2.307 inches and 2.319 inches

Mounting Hole Diameter:

0.156 inches

Scale Division Quantity:

60 single indicator single range

Overall Diameter:

Between 3.494 inches and 3.506 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

Between 3.063 inches and 3.188 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 1.244 inches and 1.256 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.744 inches and 2.756 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+60.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Band from 0 to 42 v marked lead acid 18 cell; red line at 42 v

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0