

View Online at <https://aerobasegroup.com/nsn/6625-01-111-5264>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

7.730 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 6.045 inches and 6.055 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.720 inches and 0.730 inches

Overall Height:

1.540 inches

Overall Width:

6.720 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

1.270 inches

Environmental Protection:

Dripproof and humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

5.840 inches

Meter Body Width Behind Mounting Flange:

5.435 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

Degrees f; 0; 20; 40; 60; 80; 100; 120; 140; 160; 180; 200; 220; 240; 260; 280; 300

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.190 inches

Meter Body Height Behind Mounting Flange:

1.225 inches

Features Provided:

Magnetic shield and zero adjuster

Criticality Code Justification:

Astw

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-24359

Style Designator:

Rectangular flush mtg

Supplementary Features:

Vertical mount

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0