

View Online at <https://aerobasegroup.com/nsn/6625-01-112-5300>

Circuit Current For Which Designed:

Ac

Overall Length:

2.603 inches

Mounting Stud Length:

0.500 inches

Overall Diameter:

2.816 inches

Environmental Protection:

Dustproof

Distance Between Mounting Facility Centers:

2.230 inches

Furnished Items And Quantity:

Nut 3; washer 2; insulator 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Red single indicator single range and white single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.281 inches

Meter Body Diameter Behind Mounting Flange:

2.625 inches

Background Color:

Black single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+12.0/+15.0 volts single indicator single range

Mounting Stud Diameter:

0.185 inches

Features Provided:

Self-illumination facility and zero adjuster

Circuit Attachment Method And Quantity:

1 solder lug and 3 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0